# Swivel castor with central/directional total brake:

# M18RZ-UF2K125
# (398r 29K125v K2351ZA PRIMACY)



## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Tread width | | 32 mm |
| Height | | 158 mm |
| Offset | | 40 mm |
| Stem size | | 28x100 (41°/52°) mm |
| Brake swivel radius | | 103 mm |
| Load capacity | | 150 kg |

## Technical description

| |
|---|
| die-cast aluminium load-bearing housing |
| highly polished plastic cover |
| precision ball bearings in the fork head |
| suitable for cleaning in disinfection cabins |
| smooth selection function |
| integrated selection mechanism with total locking brake "q" |
| and direction locking brake "r" |
| permanently grease filled in the switch mechanism |
| also available with electrically conductive wheel |

REACH compliant RoHS compliant

## Wheel

| |
|---|
| thermoplastic polyurethane tyre (TPU) iron grey RAL 7011, Shore A 95 plastic wheel centre and plastic thread guard, silver grey RAL 7001 precision ball bearing |

A company of Colson Group
Colson Europe Coöperatief U.A., Generatorstraat 11, 3903 LH Veenendaal,
Tel. +31 (0)318 - 536611, info@colson-europe.com