# Swivel castor with total brake mounted behind:

# BTAB 1503 6440



## Technical data

| | | |
|---|---|---|
| Diameter | | 150 mm |
| Wheel width | | 50 mm |
| Hub length | | 62 mm |
| Height | | 188 mm |
| Offset | | 53 mm |
| Top plate dimensions | | 135 x 110 mm |
| Top plate hole diameter | | 11 mm |
| Dist. between holes | | 105 x 75/80 mm |
| Brake swivel radius | | 160 mm |
| Load capacity | | 300 kg |
| Weight | | 3.1 kg |

## Technical description

| |
|---|
| Swivel fork of deep drawn zinc-coated steel |
| Swivel bearing with double ball raceways and sealring |
| with total lock brake and an extra sturdy |
| plate (4 mm) and fork legs (3.5 mm) |
| for even higher load capacity |

REACH compliant RoHS compliant

## Wheel

| |
|---|
| Aluminium wheels with black rubber tyre (Shore A 72) with two deep groove ball bearings and steel collar bushes external diameter 15/20/25 mm to internal 8/10/12 mm. Operating temperatures from -20°C to + 80°C |

A company of Colson Group
Colson Europe Coöperatief U.A., Generatorstraat 11, 3903 LH Veenendaal,
Tel. +31 (0)318 - 536611, info@colson-europe.com