# Swivel castor with total brake mounted behind:

# BTPB 1252 2101



## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Wheel width | | 38 mm |
| Hub length | | 48 mm |
| Height | | 155 mm |
| Offset | | 42.5 mm |
| Wheel axle diameter | | 15 mm |
| Top plate dimensions | | 105 x 86 mm |
| Top plate hole diameter | | 9 mm |
| Dist. between holes | | 80/77 x 60 mm |
| Brake swivel radius | | 134 mm |
| Load capacity | | 180 kg |
| Weight | | 1.8 kg |

## Technical description

| |
|---|
| Swivel fork of deep drawn zinc-coated steel |
| Swivel bearing with double ball raceways and sealring |
| with total lock brake and an extra sturdy |
| plate (4 mm) and fork legs (3.5 mm) |
| for even higher load capacity |

REACH compliant

RoHS compliant

## Wheel

| |
|---|
| Polyamide wheel with blue rubber tyre |
| (Shore A 70) with one deep groove ball bearing |

A company of Colson Group
Colson Europe Coöperatief U.A., Generatorstraat 11, 3903 LH Veenendaal,
Tel. +31 (0)318 - 536611, info@colson-europe.com