Swivel castor:

# G42AZ-RF2K100
# (367a 29K100r ZPF)

## Technical data

| | | |
|---|---|---|
| Diameter | | 100 mm |
| Tread width | | 30 mm |
| Height | | 138 mm |
| Offset | | 41,5 mm |
| Top plate dimensions | | 95x70 mm |
| Top plate hole diameter | | 9 mm |
| Dist. between holes | | 75x45/72x52 mm |
| Load capacity | | 100 kg |
| Weight | | 777 g |

## Technical description

- sheet steel metal housing
- zinc passivated
- swivel bearing with double ball race
- protected from dust and water spray with plastic seal
- available with plate PD (77x67 mm) and PF (95x70 mm)
- available with bolt hole LC (10,2 mm) and LD (12,2 mm)
- on inquiry also available with fixing pin Z522 (24x45 mm) and Z622 (28x45 mm)

REACH compliant RoHS compliant

## Wheel

- thermoplastic elastomer tyre (TPE) iron grey RAL 7011 (Shore A 80)
- plastic wheel centre and thread guard silver grey RAL7001
- precision ball bearing
- Contact discoloration on unsealed grounds possible!>>

A company of Colson Group
Colson Europe Coöperatief U.A., Generatorstraat 11, 3903 LH Veenendaal,
Tel. +31 (0)318 - 536611, info@colson-europe.com