# Swivel castor with total brake mounted behind:

# G46NZ-RF2K125-Q01
# (367h 29K125r Z522)

## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Tread width | | 32 mm |
| Height | | 157,5 mm |
| Offset | | 43,5 mm |
| Stem size | | 24x45<br>M8/19 mm |
| Load capacity | | 100 kg |

## Technical description

| |
|---|
| sheet steel metal housing |
| zinc passivated |
| swivel bearing with double ball race |
| protected from dust and water spray with plastic seal |
| available with plate PD (77x67 mm) and PF (95x70 mm) |
| available with bolt hole LC (10,2 mm) and LD (12,2 mm) |
| on inquiry also available with fixing pin Z522 (24x45 mm) and Z622 (28x45 mm) |

REACH compliant RoHS compliant

## Wheel

| |
|---|
| thermoplastic elastomer tyre (TPE) iron grey RAL 7011 (Shore A 80) |
| plastic wheel centre and thread guard silver grey RAL7001 |
| precision ball bearing |
| Contact discoloration on unsealed grounds possible!>> |

A company of Colson Group
Colson Europe Coöperatief U.A., Generatorstraat 11, 3903 LH Veenendaal,
Tel. +31 (0)318 - 536611, info@colson-europe.com