

Swivel castor with total brake mounted behind:

**G42TZ-RU2K100**  
(367h 29K100v ZPF)



## Technical data

|                         |                                                                                       |                |
|-------------------------|---------------------------------------------------------------------------------------|----------------|
| Diameter                |    | 100 mm         |
| Tread width             |    | 30 mm          |
| Height                  |    | 138 mm         |
| Offset                  |    | 41,5 mm        |
| Top plate dimensions    |    | 95x70 mm       |
| Top plate hole diameter |    | 9 mm           |
| Dist. between holes     |   | 75x45/72x52 mm |
| Load capacity           |  | 100 kg         |
| Weight                  |  | 859 g          |

## Technical description

sheet steel metal housing

zinc passivated

swivel bearing with double ball race

protected from dust and water spray with plastic seal

available with plate PD (77x67 mm) and PF (95x70 mm)

available with bolt hole LC (10,2 mm) and LD (12,2 mm)

on inquiry also available with fixing pin Z522 (24x45 mm) and Z622 (28x45 mm)



## Wheel

thermoplastic polyurethane tyre (TPU) iron grey  
RAL 7011 (Shore A 95)

plastic wheel centre and thread guard silver grey  
RAL7001

free of contact discoloration

precision ball bearing